

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
11 August 2005 (11.08.2005)

PCT

(10) International Publication Number
WO 2005/074026 A2

(51) International Patent Classification⁷: **H01L 23/00**

(21) International Application Number:
PCT/US2005/001999

(22) International Filing Date: 21 January 2005 (21.01.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
102004002982.2 21 January 2004 (21.01.2004) DE
10/838,571 4 May 2004 (04.05.2004) US
10/968,500 19 October 2004 (19.10.2004) US

(71) Applicant (for all designated States except US): **ENTHONE INC.** [US/US]; 350 Frontage Road, West Haven, CT 06516 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **XU, Chen** [US/US];
c/o Enthone Inc., 600 Route 440, Jersey City, NJ 07304


(US). **ZHANG, Yun** [US/US]; c/o Enthone Inc., 600 Route 440, Jersey City, NJ 07304 (US). **FAN, Chonglun** [CA/US]; c/o Enthone Inc., 600 Route 440, Jersey City, NJ 07304 (US). **KHASELEV, Oscar** [IL/US]; c/o Enthone Inc., 350 Frontage Road, New Haven, CT 06516 (US). **ABYS, Joseph, A.** [US/US]; c/o Enthone Inc., 350 Frontage Road, New Haven, CT 06516 (US). **WALCH, Eric** [DE/DE]; Buchner Strasse 31, 42699 Solingen (DE). **KLEINFELD, Marlies** [DE/DE]; Monhofsfield 142, 42369 Wuppertal (DE). **ECKERT, Hans, Ullrich** [DE/DE]; Hasencleverstrasse 21, 42659 Solingen (DE).

(74) Agents: **FLEISCHUT, Paul, I.J.** et al.; Senniger Powers, 1 Metropolitan Square, 16th Floor, St. Louis, MO 63102 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HN, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,

[Continued on next page]

(54) Title: PRESERVING SOLDERABILITY AND INHIBITING WHISKER GROWTH IN TIN SURFACES OF ELECTRONIC COMPONENTS



(57) Abstract: A method for reducing whisker formation and preserving solderability in tin coatings over metal features of electronic components. The tin coating has internal tensile stress and is between about 0.5 m and about 4.0 m in thickness. There is a nickel-based layer under the tin coating.

WO 2005/074026 A2



PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

- (84) **Designated States** (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

Published:

- without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.